

Keep Workers Comfortable and Safe in Extreme Temperatures

Workers in extreme temperatures wear Vortec Cooling Vests to minimize heat stress and fatigue while improving comfort and productivity.

Cold Air circulates through the Cooling Vest to distribute even cooling over the upper body.

- Vest can be worn under other protective clothing (PPE)
- Easy temperature adjustment even with gloved hands
- Provides continuous, consistent air delivery
- Vest allows for full range of motion with no airflow restrictions



Applications

Foundries
 Powder Coating
 Welding Operations
 Steel Mills
 Sand Blasting
 Asbestos Abatement

Power Plants
 Mines
 Casting Shops
 Smelters
 Boiler Rooms
 Metal Production

Paint Operations
 Forging Shops
 Hazardous Waste Removal
 Unconditioned Warehouses
 Shipyards
 Glass Plants

Vortec, an ITW Company

10125 Carver Road
 Cincinnati, Ohio 45242
 1-800-441-7475

sales@vortec.com
 www.vortec.com



How It Works


Vortec Cooling Tubes use filtered compressed air and vortex tube technology to generate cold air used for personal cooling applications.

Inside the cooling tube, a vortex tube spins the supplied compressed air, separating it into hot and cold air streams. The cold air is delivered to the Cooling Vest via a ducting tube, while the hot air exits out the other end of the PAC through a hot end muffler. Inside the vest, the cold air is circulated via the perforated lining of the vest, providing a cooling effect to the wearer of the vest and tube.

The distributed air temperature differential is +/- 60°F (33°C) from the compressed air inlet temperature.



COLD AIR DISTRIBUTION



Case Study

Cadillac of South Charlotte

Summers in South Carolina are quite hot, regularly reaching over 90°F. Inside a paint booth, this means temperatures can reach well over 100°F. Without proper PPE, heat stress, dehydration, exhaustion heat stroke can all come into play. Cadillac of South Carolina decreased those threats with the Vortec Cooling Vest.

Read more here:

<https://bit.ly/2Az7UNf>



| Item # | Description | Cooling Capacity | Compressed Air Consumption | |
|------------------|--|------------------|----------------------------|------------------|
| | | | @ 100 PSIG (SCFM) | @ 6.9 BAR (SLPM) |
| 22825 | Cooling Tube with Belt | 1500 BTU/Hr | 25 SCFM | 708 SLPM |
| 22835 | Cooling Tube with Belt | 2500 BTU/Hr | 35 SCFM | 990 SLPM |
| Cooling Vest-L | Cooling Vest (L) | 1500 BTU/Hr | 25 SCFM | 708 SLPM |
| Cooling Vest-XL | Cooling Vest (XL) | 2500 BTU/Hr | 35 SCFM | 990 SLPM |
| Cooling Vest-2XL | Cooling Vest (2XL) | 2500 BTU/Hr | 35 SCFM | 990 SLPM |
| Vest-L | Replacement Vest Only, Size Large (fits 36" to 41" girth) | | | |
| Vest-XL | Replacement Vest Only, Size X-Large (fits 41" to 46" girth) | | | |
| Vest-2XL | Replacement Vest Only, Size 2X-Large (fits 46" to 52" girth) | | | |

- Vest is made with flame resistant fabric that meets CPAI-84, Sec. 6 Fire Standard Specifications
- All Cooling Tubes have 1/4" compressed air quick connect and 3/4" garden hose thread for discharge of air to vest

Vortec, an ITW Company

10125 Carver Road
Cincinnati, Ohio 45242
1-800-441-7475

sales@vortec.com
www.vortec.com

